

微電腦多功能高速離心機




全新型高速桌上離心機 model : 5430

- 不同八種轉子可任意搭配，適合各種實驗
- 最高離心力可達 30000 (g)
- 可儲存 50 種操作模式
- 體積小不佔空間
- 全新 FA-45-24-11 Kit 轉子，讓您輕鬆使用 column-spin



- **FA-45-30-11**
Standard rotor** for
30 × 1.5 / 2.0 ml tubes



- **F-45-30-11**
Rotor** for
30 × 1.5 / 2.0 ml tubes



- **FA-45-24-11-HS**
High-speed rotor** for
24 × 1.5 / 2.0 ml tubes



- **FA-36-6-30**
Rotor for 6 × 15 / 50 ml
Falcon® tubes



- **FA-45-24-11-Kit**
Rotor** for 24 × open 1.5 / 2.0 ml
micro test tubes, e.g. spin columns



- **F-45-64-5-PCR**
PCR strip rotor for up to
64 × 2.0 ml tubes



- **F-45-18-17-Cryo**
Rotor for Cryotubes®



- **A-2-MTP**
Swing-bucket rotor for MTP
and PCR plates

Rotor	Tubes / plates	Properties	Max. g-force	Max. speed
FA-45-30-11, standard rotor	30 × 1.5 / 2.0 ml micro test tubes	aerosol-tight* and coated**	20,817 × g	14,000 rpm
FA-45-30-11, micro test tube rotor	30 × 1.5 / 2.0 ml micro test tubes	coated**	20,817 × g	14,000 rpm
F-45-30-11-HS, high-speed rotor	24 × 1.5 ml Eppendorf Safe-Lock tubes and 3810 × tubes and coated**	aerosol-tight*	30,130 × g	17,500 rpm
FA-45-24-11-Kit, Kit rotor	24 × filter tubes / spin columns, nucleic acid purification kits, micro test tubes up to 2.0 ml	aerosol-tight*	19,090 × g	13,200 rpm
F-45-64-5-PCR, PCR tube strip rotor	8 × 5 / 8-Strip PCR tubes or 64 × individual 0.2 ml PCR tubes	-	13,543 × g	11,800 rpm
F-45-18-17-Cryo, CryoTube rotor	18 × 1.1 / 2.0 ml CryoTube®	-	8,320 × g	8,900 rpm
F-35-6-30, Falcoff® tube rotor	6 × 50 ml or 6 × 15 ml Falcon® tubes	-	7,197 × g	7,830 rpm
A-2-MTP, MTP rotor	MTP, PCR plates, CombiSlid® adapter, max. loading height 29 mm	-	2,204 × g	4,680 rpm